
Verification of Conformity

No. ESTS-P21122806-M1

The following products have been tested by us with the listed standards and found in compliance with the council Low Voltage Directive 2014/35/EU. It is possible to use CE marking to demonstrative for the compliance with this Directive.

Applicant	: Associated Industries China, Inc
Address	: 5F-1, No.3-1, Park Street, Nangang District, Taipei, 11503, Taiwan
Product	: LCD Display
Trade Mark	: AG Neovo
Model No.	: QX-32x (x can be A-Z, a-z, 0-9, "+", "-", "/", "\" or blank)



EST Technology Co., Ltd. Http://www.gdest.cn; Tel: +86 769-83081888 Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

John Lan Manager Date: Jan.10, 2025

The statement is based on a single evaluation of one sample of above mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab's logo.



Audio/video, info	TEST REPORT EN 62368-1 and BS EN 62368-1 prmation and communication technology equipment Part 1: Safety requirements	
Report reference No	ESTS-P21122806-M11081	
Tested by (printed name and signature)	MorrisLi Morrisciente	
Approved by (printed name and signature)	Tom Nie Je Viel	
Date of issue	2025-01-10 Tuthor 10	
Testing laboratory	EST Technology Co., Ltd.	
Address	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China	
Test location	Same as above	
Applicant's name:	Associated Industries China, Inc	
Address	5F-1,No.3-1,Park Street,Nangang District,Taipei,11503,Taiwan	
Manufacturer	Same as applicant	
Address	Same as applicant	
Standard:	EN 62368-1:2014+A11:2017 BS EN 62368-1:2014+A11:2017	
Test procedure	LVD and UKCA	
Non-standard test method:	N/A	
Type of test equipment	LCD Display	
Trade mark	AGNeovo	
Model/Type designation	QX-32x (x can be A-Z, a-z, 0-9, "+", "-", "/", "\" or blank)	
Rating	Input: 100-240V~, 50/60Hz, 0.55A	
TRF originator	EST Technology Co., Ltd.	
Copyright blank test report:	EST Technology Co., Ltd.	
Test item particulars:		
Equipment mobility	Stationary and wall-mounted apparatus	
Operating Condition	Continuous	
Tested for IT power systems	No	
Class of equipment	Class I equipment	
Mass of equipment (kg)	Approx.15.7kg	
Protection against ingress of water	IPX0	



List of Attachments (including a total number of pages N/A	in each attachment):
Summary of testing:	
Tests performed (name of test and test clause): N/A	Testing location: N/A



Copy of marking plate:	
	Aneovo
	LCD Display/液晶顯示器 Model No./型號: QX-32
	Input Rating/输入電源: 100-240V~, 50/60Hz, 0.55A
	Apparaten skall anslutas till jordat uttag. Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan. Apparatet må tilkoples jordet stikkontakt. Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord. CAN ICES-3(B)/NMB-3(B) FEE EEEE A A A A A A A A A A A A A A A A
	Manufacturer: Associated Industries China, Inc. 5F-1, No.3-1, Park Street, Nangang District, Taipei, 11503, Taiwan Importer: AG Neovo Technology B.V. Molenbaan 9 2908 LL Capelle a/d IJssel, The Netherlands
	P/N: XXXXXXXXXXXX
	S/N: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
ON/OFF POWER	DVI HDMI DP VGA AUDIO F/W LAN RS232 IN Update

Remark:

- 1. This is representative label, the other models are identical to them except for the model name.
- 2. The above markings are the minimum requirements required by the safety standard. For the final production, the additional markings which do not give rise to misunderstanding may be added.
- 3. The CE marking and WEEE symbol should be at least 5.0mm and 7.0mm respectively in height.
- 4. The mfr. and importer's name and address should be printed on label, if not possible can be printed onpackage or a document accompanying the equipment.
- 5. For some special national requirement, the USB rating shall be provided on marking but will not listed in page 1 ratings.



TEST ITEM PARTICULARS:		
Classification of use by	Ordinary person	
	Skilled person	
Supply Connection	AC Mains DC Mains	
Supply Connection	External Circuit - not Mains connected	
Supply % Tolerance	⊠+10%/-10%	
	+20%/-15%	
	└── + %/%	
	None	
Supply Connection – Type:	➢ pluggable equipment type A - □non-detachable supply cord	
	Appliance coupler	
	direct plug-in	
	mating connector	
	pluggable equipment type B -	
	non-detachable supply cord	
	appliance coupler	
	<pre>permanent connection mating connectorother:</pre>	
Considered current rating of protective device as part	16A (13A for United Kingdom)	
of building or equipment installation	Installation location: 🖂 building; 🗌 equipment	
Equipment mobility:	movable hand-held transportable stationary for building-in direct plug-in rack-mounting wall-mounted	
Over voltage category (OVC)		
	OVC IV	
Class of equipment:	Class I Class II Class III	
Access location:	restricted access location X/A	
Pollution degree (PD):	□ PD 1 ⊠ PD 2 □ PD 3	
Manufacturer's specified maximum operating ambient	40°C	
IP protection class	□ IPX0 □ IP	
Power Systems	⊠ TN □ TT□ IT - 230 V _{L-L}	
Altitude during operation (m)	☐ 2000 m or less ⊠ Up to 5000 m	
Altitude of test laboratory (m)	⊠ 2000 m or less □ m	
Mass of equipment (kg)	Approx. 15.7kg	



POSSIBLE TEST CASE VERDICTS:				
- test case does not apply to the test object:	N/A			
- test object does meet the requirement :	P (Pass)			
- test object does not meet the requirement :	F (Fail)			
TESTING:				
Date of receipt of test item:	N/A			
Date (s) of performance of tests:	N/A			
GENERAL REMARKS:				
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a 🗌 comma / 🖄 point is used as the decimal separator.				
Name and address of factory (ies)	1.Candid International (Fujian) Co.,LTD.			
	Changshan Overseas Chinese Economic Development Industrial Zone,Zhangzhou City,Fujian,CHINA			
	2.SHENZHEN FACSION ELECTRONICS CO., LTD FLOOR 3, 4 & 5, BUILDING B, DONGZHIJIA INDUSTRIAL PARK, LEZHUJIAO, HUANGMABU, HANGCHENG STREET, BAO'AN DISTRICT, SHENZHEN,P.R.CHINA			
GENERAL PRODUCT INFORMATION:				
Product Description:				
1. The sample(s) tested complies with the requirements of EN 62368-1:2014+A11:2017 and BS EN 62368- 1:2014+A11:2017;				
2. The equipment models QX-32x (x can be A-Z, a-z, 0-9, "+", "-", "/", "\" or blank) were Audio/Video,information and communication technology equipment;				
The product's rear enclosure is secured to front enclosure by screws;				
4. Specified maximum ambient temperature is 40°C, this apparatus applied for 5000m altitude max;				
5. This product consists of:				
1) Built-in switching power supply; 2) Signal and data ports; 3) LCD Panel; 4)Two speakers (8 Ω x2),				

- 5) Optional rack mounting set;
- 6. The test items are pre-production samples without serial numbers;
- 7. All these models are same as each other only except for the model name, appearance in color and silkscreen and marketing purpose;
- 8. USB terminals only for firmware upgrades and this terminal can not load.
- 9. The model QX-32 was selected for all testing.
- 10. The screen with the handle is for panel maufacture is AUO, The screen without the handle is r panel maufacture is BOE.

Report Summary:

- This Test Report should be read in conjunction with the original report.

History:



Ref. No. ESTS-P21122806, date 2022-01-19 (Original test report);

Ref. No. ESTS-P21122806-M1, date 2025-01-08 (1st Modification)

Description of technical change(s):

1. Added a new factory.

For the above described modification(s) the following testing were considered to be necessary:

Change	Testing	Comments
1, 2	N/A	N/A