

## VA-3201 32-INCH FULL HD LCD DISPLAY












## **FEATURES**


- Full HD 1920 x 1080 resolution
- 300 nits brightness for indoor public use
- 4000:1 contrast ratio makes the picture look brighter and richer
- 178°/178° wide viewing angle ensures your content is easily visible from almost any angle
- Versatile connectivity: VGA, HDMI, and DisplayPort inputs
- Built-in dual 3W speakers, audio input and output ports
- Support landscape and portrait wall-mounted installation
- Ideal for 16/7 commercial operation

The VA-3201 is a 32" Full HD LCD display engineered for essential digital signage applications. Featuring sharp 1080p resolution, expansive viewing angles, and a high contrast ratio, it delivers dynamic visual content in indoor environments. Its versatile connectivity options and integrated audio capabilities enable seamless connections to media players and various multimedia devices, providing an immersive visual and audio experience. The display supports both desk placement and mounting in landscape or portrait orientations, making it an ideal solution for retail, corporate, and other indoor commercial spaces.

## TECHNICAL DRAWING









## **SPECIFICATIONS**

Panel	
Panel Type	VA
Panel Size	31.5"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.364 mm
Brightness	300 cd/m <sup>2</sup>
Contrast Ratio	4000:1
Viewing Angle (H/V)	178°/178°
Display Colour	16.7M
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze25%), 3H Hard Coating
Frequency	3
Frequency (H)	30 KHz-83 KHz
Frequency (V)	56 Hz-75 Hz
Signal Input	
DisplayPort	x1
HDMI	1.4 x 1
VGA	15-Pin D-Sub x 1
Audio	10-1 III D-000 X 1
	Storag Audio Jook (2.5 mm)
Audio In Audio Out	Stereo Audio Jack (3.5 mm)
	Stereo Audio Jack (3.5 mm)
Internal Speakers	3W x 2
Power	
Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	27W
Standby Mode	< 0.5W
Off Mode	< 0.3W
Operating Conditions	
Temperature	5°C-35°C (41°F-95°F)
Humidity	20%-85% (non-condensing)
Storage Conditions	
Temperature	-20°C-60°C (-4°F-140°F)
Humidity	5%-85% (non-condensing)
Mounting	
VESA FPMPMI	Yes (100 x 100 mm)
Stand	
Tilt	-5° to 8°
Security	
Kensington Security Slot	Yes
Dimensions	
Product with Base (W x H x D)	714.0 x 485.2 x 200.9 mm (28.1" x 19.1 " x 7.9")
Product w/o Base (W x H x D)	714.0 x 423.7 x 54.1 mm (28.1" x 16.7" x 2.1")
Packaging (W x H x D)	799.0 x 530.0 x 140.0 mm (31.5" x 20.9" x 5.5")
Weight	
Product with Base	7.2 kg (15.9 lb)
Product w/o Base	5.7 kg (12.6 lb)
Packaging	9.5 kg (20.9 lb)
Regulation Approval	
Certifications & Compliance	CE, LVD, WEEE, RoHS, REACH, EAC
Accessories	
Supplied	Power Cord, HDMI Cable, Quick Start Guide
Optional Accessories	
Ceiling Mount (Landscape only)	CMP-01 + LMK-02, CMP-01 + WMK-03
Wall Mount (Landscape only)	WMA-01, LMK-02, WMK-01, WMK-03, PMK-01
Desk Mount (Landscape only)	DMC-01, ES-02













